

						Rev.
1	Item				3	
2	DUTY				Level Switches	
3	INSTALLATION LOCATION				OUTDOOR	
4	INSTALLATION METHOD				-	
5	AMBIENT TEMP MIN / MAX				-20 °C / 48 °C	
6	<b>CABLE TECHNICAL DATA</b>					
7	MAKE				LATER	
8	TYPE				As per EN50288-7	
9	CONDUCTORS				Stranded Copper - IEC 60228 class 2	
10	INSULATION				XLPE	
11	CORE / PAIR / TRIAD				Twisted Pair	
12	IDENTIFICATION				Black - white	
13	SCREENING				Collective Aluminium/Maylar tape + tinned copper drain wire	
14	BEDDING				PVC	
15	ARMOUR				Galvanised Steel Wire Armour (SWA)	
16	OUTER JACKET				PVC	
17	OUTER SHEATH COLOUR				Gray	
18	CROSS SECTION				1.5 mm <sup>2</sup>	
19	NUMBER OF CORES / PARE / TRIADS				2 Pair	
20	MAX. OPERATING VOLTAGE				300 / 500 Volt	
21	MIN. OPERATING TEMPERATURE				-20 °C	
22	MAX. OPERATING TEMPERATURE				+60 °C	
23	CONDUCTOR MAXIMUM TEMPERATURE				+90 °C	
24						
25	INNER SHEATH DIAMETER				Later	
26	OUTER SHEATH DIAMETER				Later	
27						
28	FLAME RETARDANT				IEC60332-1-2 / IEC 60332-3-24 (cat.C)	
29						
30						
31						
32						
33						
34						
35						