









OWNER:  شرکت سست موبلی آفس ابراهیمان (سهانی نخسیر)	BUSHEHR PETROCHEMICAL COMPANY MEG PLANT						EPC CONTRACTOR:  Chagalesh-Enerchimi-Steam Joint Venture BUPC-MEG PLANT PROJECT		
	MAIN OIL PUMP MECHANICAL DATA SHEET FOR EMERGENCY INSTRUMENT AIR COMPRESSOR								
MC : 	Project	Area	Phase	Unit	Dis.	Doc.	Seq.	Contract No : 52-98/445	
Owner Document Number: 17811-11K	BU	20	VD	303	ME	DSH	0072	Rev.:	Page
								03	1 of 3

MAIN OIL PUMP MECHANICAL DATA SHEET FOR EMERGENCY INSTRUMENT AIR COMPRESSOR

 شرکت سست موبلی آفس ابراهیمان (سهانی نخسیر)	 Chagalesh-Enerchimi-Steam Joint Venture BUPC-MEG PLANT PROJECT	BUSHEHR PETROCHEMICAL COMPANY MEG PLANT
Document Review		
Issue Purpose:	AB	
Result Code: AP,AN,CM,RE,NC	AP	
Next Status : IFC,IFA,IFI,AFC,AB	-	
Responsible Department	MECHANIC	
Commented Date	Apr.30.2023	
Approval or review hereunder shall not be construed to relieve Vendor / Subcontractor of his responsibilities and liability under the contract.		

03	26/04/2023	As Built	KP	LdM	CL	
02	07/01/2022	Approved for Construction	KP	LdM	CL	
01	15/12/2021	For approval	KP	LdM	CL	
00	16/11/2021	For approval	KP	LdM	CL	
Rev	Date	Purpose of Issue	Prepared	Checked	Approved	AC Code
.						
					Class: 1	Phase: P

VENDOR 		MAIN OIL PUMP MECHANICAL DATA SHEET FOR EMERGENCY INSTRUMENT AIR COMPRESSOR		P.O. No. 52-98/445		
				Document No. 17811-11K		
				Sheet No. 3		
				Rev.No 03		
CONTRACTOR / END USER 			BUSHEHR PETROCHEMICAL COMPANY MEG PLANT			
					Service instrument air compressor 20-C-7080	
SHAFT DRIVEN OIL PUMP						
1						
2	No. Required	1				
3	MFR Supplier	Mehrer				
4	Type of Pump :	Gear Pump (Shaft driven)				
5	Oil Type (Pumping Fluid) :	Klüber Summit PS300				
6	Capacity :	30 - 50 L/h				
7	Min.. Oil Temperature :	5 °C				
8	Max. Oil Temperature :	70 °C				
9	Max. Allowable Oil Pressure / MAWP :	1 bar(g)				
10	Min. Allowable Oil Pressure :	0,5 bar(g)				
11	Operating Oil Pressure :	0,7 bar(g)				
12	PRV Set Pressure :	0,7 bar(g)				
13	Location :	Rear bearing cover				
14	Material of pump :	SS gear and Nodular iron body				
15	Design Temperature :	-5 to 85°C				
16	Design pressure	3.5 bar(g)				
17	RPM of Pump	Gear driven so not applicable				
18	Design	manufacturer standard				
19	NOTES : The real conditions depends on the environmental temperatures and the working conditions as speed and duty circle.					